D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Smelko
Date of Inspection: Nov 1.15	Time: 5:00
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Unit Down

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down /	0	0		A	N	—	—	—
SDS Shredder	Running	Down /	1:12	1:1		A	N	—	—	—
ATDU / OWS	Running	Down /	9829	4.1	2.5	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running /	Down ~~/~~	2111	5.0	2.3	A	N	—	—	—
Distillation Unit	Running /	Down	~~1169~~	2.9	3.4	A	N	—	—	—
Tank 51	Running /	Down	2600	3.9	3.1	A	N	—	—	—
Tank 55	Running /	Down	9999	5.2	7.2	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Chema Saucedo
Date of Inspection: 10/1/15	Time: 530pm
Shift: (First) or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR (FLARE*)	Running X	Down	O	O		A	N	-	-	—
SDS Shredder	Running	Down X	98	.1		A	N	-	-	—
ATDU / OWS	Running X	Down	7849	3.1	1	A	N	-	-	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running X	Down	2098	4.7	1.7	A	N	-	-	—
Distillation Unit	Running X	Down	1029	2.8	1.3	A	N	-	-	—
Tank 51	Running X	Down	2647	2.8	1.4	A	N	-	-	—
Tank 55	Running X	Down	8714	4.7	3	A	N	-	-	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Paul Lark	
Date of Inspection: 11-2-15	Time: 5:00 AM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100ppm	
Background Instrument Reading: 0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	n	–	–	–
SDS Shredder	Running ✓	Down	89	.1		A	n	–	–	–
ATDU / OWS	Running ✓	Down	7840	.2	.9	A	n	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2096	4.5	1.7	A	n	–	–	–
Distillation Unit	Running ✓	Down	1031	3.0	1.4	A	n	–	–	–
Tank 51	Running ✓	Down	2650	2.6	1.2	A	n	–	–	–
Tank 55	Running ✓	Down	8717	4.8	.9	A	n	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ruben Moland III	
Date of Inspection: 10/[illegible]/15	Time: 5:00 am
Shift: (First or Second) — First circled	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: 100ppm Isobutylene	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Date	Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE* (CARBON circled)	Running (circled)	Down	0	0		A	N	—	—	—
SDS Shredder	Running (circled)	Down	90	.2		A	N	—	—	—
ATDU / OWS	Running (circled)	Down	7843	.03	1.0	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running (circled)	Down	2100	4.6	1.8	A	N	—	—	—
Distillation Unit	Running (circled)	Down	1033	3.1	1.5	A	N	—	—	—
Tank 51	Running (circled)	Down	2652	2.7	1.3	A	N	—	—	—
Tank 55	Running (circled)	Down	8721	4.9	1.0	A	N	—	—	—

Revised 5/1/2015

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Jaime N Cocoia
Date of Inspection: 11/3/15	Time: 5 AM
Shift: (First or Second)	
Monitor ID: Minirae 2000	
Instrument Calibration Gases: Isobutylene 100ppm	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	94	.3		A	N	—	—	—
ATDU / OWS	Running ✓	Down	7856	1.1	.7	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2113	4.7	1.3	A	N	—	—	—
Distillation Unit	Running ✓	Down	1040	3.1	1.6	A	N	—	—	—
Tank 51	Running ✓	Down	2648	2.0	1.2	A	N	—	—	—
Tank 55	Running ✓	Down	8713	4.8	.6	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ruben Niland
Date of Inspection:	10/2/2015 Time: 5:00 PM
Shift: (First or Second)	2nd
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	100 ppm Isobutylene
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	96	.5		A	N	—	—	—
ATDU / OWS	Running ✓	Down	7877	1.4	.8	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2119	4.9	1.5	A	N	—	—	—
Distillation Unit	Running ✓	Down	1045	3.2	1.7	A	N	—	—	—
Tank 51	Running ✓	Down	2659	2.1	1.3	A	N	—	—	—
Tank 55	Running ✓	Down	8723	4.9	.7	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Jaime N Cocera
Date of Inspection: 11/4/15	Time: 5 Am
Shift: (First or Second)	
Monitor ID:	Minitae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	101	.7		A	N	—	—	—
ATDU / OWS	Running ✓	Down	7883	1.6	.7	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2130	5.1	1.2	A	N	—	—	—
Distillation Unit	Running ✓	Down	1051	3.1	1.9	A	N	—	—	—
Tank 51	Running ✓	Down	2675	2.4	1.2	A	N	—	—	—
Tank 55	Running ✓	Down	8732	5.2	.4	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Paul Lark
Date of Inspection: 11-4-15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	102	.7		A	N	—	—	—
ATDU / OWS	Running	Down	1455	1.7	1.1	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	210	8.1	1.2	A	N	—	—	—
Distillation Unit	Running	Down	1046	3.0	2.0	A	N	—	—	—
Tank 51	Running	Down	2676	2.5	1.1	A	N	—	—	—
Tank 55	Running	Down	9591	5.1	3	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: George A Sanchez	
Date of Inspection: 11/5/15	Time: 5:00 Am
Shift (First or Second)	
Monitor ID: Min Rae 2000	
Instrument Calibration Gases: Isobutylene 100ppm	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	Ø	Ø		A	N	–	–	–
SDS Shredder	Running ✓	Down	284	.9		A	N	–	–	–
ATDU / OWS	Running ✓	Down	8217	1.9	1.1	A	N	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2486	5.3	1.3	A	N	–	–	–
Distillation Unit	Running	Down ✓	126	1.8	1.4	A	N	–	–	–
Tank 51	Running ✓	Down	3172	2.8	1.5	A	N	–	–	–
Tank 55	Running ✓	Down	8786	5.4	.4	A	N	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Paul Lark
Date of Inspection: 11-5-15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100 ppm
Background Instrument Reading:	0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	101	.8		A	N	—	—	—
ATDU / OWS	Running ✓	Down	7861	1.7	1.3	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	227	5.0	1.3	A	N	—	—	—
Distillation Unit	Running ✓	Down	1056	3.1	1.9	A	N	—	—	—
Tank 51	Running ✓	Down	2670	1.0	1.0	A	N	—	—	—
Tank 55	Running ✓	Down	8721	5.8	.5	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Chema Sawcedo	
Date of Inspection: 11/6/15	Time: 5AM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100ppm	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	O	O		A	N	-	-	—
SDS Shredder	Running ✓	Down	197	2.0		A	N	-	-	—
ATDU / OWS	Running ✓	Down	1341	1.7	—	A	N	-	-	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1247	4.2	2.4	A	N	-	-	—
Distillation Unit	Running ✓	Down ✓	1098	3.2	1.8	A	N	-	-	—
Tank 51	Running ✓	Down	1541	2.7	1.5	A	N	-	-	—
Tank 55	Running ✓	Down	1672	4.1	2.4	A	N	-	-	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Paul Lorke	
Date of Inspection: 1-6-15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100 ppm	
Background Instrument Reading: 0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	n	—	—	—
SDS Shredder	Running	Down	102	.9		A	n	—	—	—
ATDU / OWS	Running	Down	7870	1.7	1.2	A	n	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2112	4.8	1.5	A	A	—	—	—
Distillation Unit	Running	Down	1055	3.2	2.1	A	n	—	—	—
Tank 51	Running	Down	2670	1.2	1	A	n	—	—	—
Tank 55	Running	Down	5750	5.6	.3	A	n	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Chema Saucedo
Date of Inspection: 11/7/15	Time: 5AM
Shift: (First or (Second))	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR (FLARE*)	Running ✓	Down	0	0		A	N	–	–	—
SDS Shredder	Running ✓	Down	217	1.2		A	N	–	–	—
ATDU / OWS	Running ✓	Down	1541	1.8	—	A	N	–	–	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3115	2.7	.5	A	N	–	–	—
Distillation Unit	Running ✓	Down	1127	3.7	2.1	A	N	–	–	—
Tank 51	Running ✓	Down	3247	6.0	3.4	A	N	–	–	—
Tank 55	Running ✓	Down	8053	4.7	2.1	A	N	–	–	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ruben Hdanck
Date of Inspection: 11/7/2015	Time: 5:00pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100 ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	221	1.4		A	N	—	—	—
ATDU / OWS	Running	Down	1559	1.9	—	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	3190	2.9	.6	A	N	—	—	—
Distillation Unit	Running	Down	1141	3.8	2.2	A	N	—	—	—
Tank 51	Running	Down	3964	6.1	3.5	A	N	—	—	—
Tank 55	Running	Down	8679	4.8	2.2	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: M. PHILLIPS	
Date of Inspection: 11-8-15	Time: 5 AM
Shift: (First or Second)	
Monitor ID: MINI RAE 2000	
Instrument Calibration Gases: ISOBUTYLENE 100 PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	219	1.3		A	N	—	—	—
ATDU / OWS	Running	Down	1561	1.9	0	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	3183	2.8	.6	A	N	—	—	—
Distillation Unit	Running	Down	1151	3.9	2.1	A	N	—	—	—
Tank 51	Running	Down	3270	6.0	3.4	A	N	—	—	—
Tank 55	Running	Down	8704	4.9	2.3	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ryben Noland
Date of Inspection: 11/8/15	Time: 5:00pm
Shift: (First or Second)	
Monitor ID:	MiniRae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status	Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
						Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	(Running) Down	Ø	Ø		A	N	—	—	—
SDS Shredder	(Running) Down	219	1.4		A	N	—	—	—
ATDU / OWS	(Running) Down	1565	1.9	Ø	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	(Running) Down	3190	2.9	0.9	A	N	—	—	—
Distillation Unit	(Running) Down	1171	4.0	2.1	A	N	—	—	—
Tank 51	(Running) Down	3281	6.1	3.5	A	N	—	—	—
Tank 55	(Running) Down	8711	4.8	2.4	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	M. PHILLIPS
Date of Inspection:	11-9-15
Time:	5 AM
Shift: (First or Second)	Second
Monitor ID:	MINI RAE 2000
Instrument Calibration Gases:	ISOBUTYLENE 100 PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	218	1.2		A	N	—	—	—
ATDU / OWS	Running	Down	1549	1.7	0	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	—	—	—	A	N	→	→	DRUM + CARBON TOTES NEED REPLACEMENT
Distillation Unit	Running	Down	—	—	—	—	—	—	—	—
Tank 51	Running	Down	3297	6.2	3.8	A	N	—	—	—
Tank 55	Running	Down	8802	4.9	2.4	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Paul Lark	
Date of Inspection: 11-9-15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100 ppm	
Background Instrument Reading: 0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	n	–	–	–
SDS Shredder	Running	Down	219	1.5		A	n	–	–	–
ATDU / OWS	Running	Down	1544	1.9	0	A	n	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	3188	2.8	.9	A	n	–	–	–
Distillation Unit	Running	Down	1177	3.8	2.2	A	n	–	–	–
Tank 51	Running	Down	3071	5.8	3.6	A	n	–	–	–
Tank 55	Running	Down	8715	4.7	3.0	A	n	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	George A Sanchez
Date of Inspection: 11/10/15	Time: 5:00 AM
Shift: First or Second	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	Ø	Ø		A	N	–	–	–
SDS Shredder	Running ✓	Down	286	1.7		A	N	–	–	–
ATDU / OWS	Running ✓	Down	2182	2.1	Ø	A	N	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2997	2.9	1.1	A	N	–	–	–
Distillation Unit	Running ✓	Down	1262	4.0	2.4	A	N	–	–	–
Tank 51	Running ✓	Down	3254	5.9	3.8	A	N	–	–	–
Tank 55	Running ✓	Down	8347	5.1	3.2	A	N	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Paul Lark	
Date of Inspection: 11-10-15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100 ppm	
Background Instrument Reading: 0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ~	Down	0	0		A	n	—	—	—
SDS Shredder	Running	Down	2.8	1.6		A	n	—	—	—
ATDU / OWS	Running	Down	1571	2.0	.1	A	n	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	3200	2.8	.8	A	n	—	—	—
Distillation Unit	Running	Down	1182	4.0	2.3	A	n	—	—	—
Tank 51	Running	Down	3886	6.1	3.3	A	n	—	—	—
Tank 55	Running	Down	8748	4.7	2.5	A	n	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	George A Sanchez
Date of Inspection: 11/11/15	Time: 5:00pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down ✓	0	0		A	N	–	–	–
SDS Shredder	Running	Down ✓	27.9	.8		A	N	–	–	–
ATDU / OWS	Running ✓	Down	1687	2.2	0	A	N	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3349	3.0	1.1	A	N	–	–	–
Distillation Unit	Running ✓	Down	1312	4.2	2.7	A	N	–	–	–
Tank 51	Running ✓	Down	3515	6.4	3.9	A	N	–	–	–
Tank 55	Running ✓	Down	8126	4.8	2.7	A	N	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ruben Noland
Date of Inspection:	Time: 500
Shift: (First or Second)	
Monitor ID:	MiniRae 3000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	Ø	Ø		A	N	—	—	—
~~SDS~~ Shredder	Running	Down	16.1	.7		A	N	—	—	—
ATDU / OWS	Running	Down	1664	2.0	6	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	3310	2.6	.9	A	N	—	—	—
Distillation Unit	Running	Down	1360	4.0	2.5	A	N	—	—	—
Tank 51	Running	Down	3471	5.9	3.7	A	N	—	—	—
Tank 55	Running	Down	8091	4.3	2.5	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Jaime N Cocera
Date of Inspection: 11/12/15	Time: 5AM
Shift: (First or Second)	
Monitor ID:	MiniRae 2000
Instrument Calibration Gases:	Isobutylene 100 PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	–	–	–
SDS Shredder	Running	Down ✓	1710	1.2		A	N	–	–	–
ATDU / OWS	Running ✓	Down	3370	2.6	0	A	N	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1341	3.4	1.3	A	N	–	–	–
Distillation Unit	Running ✓	Down	1360	4.7	3.6	A	N	–	–	–
Tank 51	Running ✓	Down	3540	6.6	3.5	A	N	–	–	–
Tank 55	Running ✓	Down	8172	5.2	2.7	A	N	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ruben Mollard
Date of Inspection: 11/18/15	Time: 5:00pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	1690	.9		A	N	—	—	—
ATDU / OWS	Running	Down	3361	2.3	0	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1329	3.2	1.2	A	N	—	—	—
Distillation Unit	Running	Down	1351	4.3	2.9	A	N	—	—	—
Tank 51	Running	Down	3528	6.5	3.9	A	N	—	—	—
Tank 55	Running	Down	8165	4.8	2.8	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Jaime N Garcia
Date of Inspection: 11/13/15	Time: 5 PM
Shift: (First or Second)	
Monitor ID:	Minitae 2000
Instrument Calibration Gases:	Isobutylene 100 ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	-	-	—
SDS Shredder	Running	Down ✓	3.1	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1931	2.7	.1	A	N	-	-	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1886	1.1	.5	A	N	—	—	—
Distillation Unit	Running ✓	Down	911	3.6	1.7	A	N	-	-	—
Tank 51	Running ✓	Down	871	1.3	1.1	A	N	-	—	—
Tank 55	Running ✓	Down	33.3	2.4	2.3	A	N	—	-	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ruben Hdard
Date of Inspection: 11/13/15	Time: 500pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Propylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	3.2	0		A	N	—	—	—
ATDU / OWS	Running	Down	1940	2.8	.2	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1893	1.3	.7	A	N	—	—	—
Distillation Unit	Running	Down	423	3.7	1.9	A	N	—	—	—
Tank 51	Running	Down	879	1.5	1.4	A	N	—	—	—
Tank 55	Running	Down	6315	2.6	2.5	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Jaime N Cocerca
Date of Inspection: 10/14/15	Time: 5Am
Shift: (First or Second)	
Monitor ID:	Minirae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	3.5	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1952	3.1	.2	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1901	1.6	.6	A	N	—	—	—
Distillation Unit	Running ✓	Down	441	3.4	2.2	A	N	—	—	—
Tank 51	Running ✓	Down	883	1.6	1.5	A	N	—	—	—
Tank 55	Running ✓	Down	8327	3.3	2.3	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Paul Lantz	
Date of Inspection: 11-24-15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100 ppm	
Background Instrument Reading: 0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	-	-	-
SDS Shredder	Running	Down	3.5	0		A	N	-	-	-
ATDU / OWS	Running	Down	1950	2.9	.1	A	N	-	-	-
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1808	1.1	.7	A	N	-	-	-
Distillation Unit	Running	Down	440	3.3	2.1	A	N	-	-	-
Tank 51	Running	Down	880	1.6	1.4	A	N	-	-	-
Tank 55	Running	Down	532	3.1	2.2	A	N	-	-	-

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Chema Saucedo	
Date of Inspection: 11-15-15	Time: 6Am
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100 ppm	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running X	Down	0	0		A	N	-	-	—
SDS Shredder	Running X	Down	112	.4		A	N	-	-	—
ATDU / OWS	Running X	Down	1147	-	.7	A	N	-	-	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running X	Down	1047	7.8	2.7	A	N	-	-	—
Distillation Unit	Running	Down X	100	2.1	0	A	N	-	-	—
Tank 51	Running X	Down	1247	3.4	.7	A	N	-	-	—
Tank 55	Running X	Down	1371	2.7	.8	A	N	-	-	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Paul Lafe
Date of Inspection: 11-15-16	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100 ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	–	–	–
SDS Shredder	Running	Down	120	.3		A	N	–	–	–
ATDU / OWS	Running	Down	1950	1.01	1.7	A	N	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1850	2.2	0.7	A	N	–	–	–
Distillation Unit	Running	Down	450	3.1	2.1	A	A	–	–	–
Tank 51	Running	Down	900	1.6	1.4	A	N	–	–	–
Tank 55	Running	Down	9410	2.1	2.2	A	N	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Alex Bautista
Date of Inspection: 11/16/15	Time: 5 Am
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running 1	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	115	.08		A	N	—	—	—
ATDU / OWS	Running	Down	1138	1.02	1.6	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1032	2.6	0.7	A	N	—	—	—
Distillation Unit	Running	Down	100	2.2	0	A	N	—	—	—
Tank 51	Running	Down	1222	3.5	1.2	A	N	—	—	—
Tank 55	Running	Down	1311	2.7	.9	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ruben Noland III
Date of Inspection: 11/6/15	Time: 5:00pm
Shift: (First) or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	(Running)	Down	Ø	Ø		A	N	—	—	—
SDS Shredder	Running	(Down)	123	.4		A	N	—	—	—
ATDU / OWS	Running	(Down)	1957	1.1	1.8	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	(Down)	1359	2.3	0.7	A	N	—	—	—
Distillation Unit	Running	(Down)	469	3.1	2.1	A	N	—	—	—
Tank 51	Running	(Down)	903	1.7	1.5	A	N	—	—	—
Tank 55	Running	(Down)	9435	2.2	2.3	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Jaime N Garcia
Date of Inspection:	11/7/15
Time:	5AM
Shift: (First or Second)	
Monitor ID:	Minirae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	130	1.0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1961	.9	1.6	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1853	2.7	.8	A	N	—	—	—
Distillation Unit	Running ✓	Down	470	3.3	2.4	A	N	—	—	—
Tank 51	Running ✓	Down	910	2.1	1.9	A	N	—	—	—
Tank 55	Running ✓	Down	9431	2.6	2.5	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ruben Holand III
Date of Inspection: 11/17/15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100 ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	(Down)	0	0		A	N	—	—	—
(CARBON OR FLARE*) SDS Shredder	Running	(Down)	1995	1.1		A	N	—	—	—
ATDU / OWS	(Running)	Down	1964	1.0	1.7	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	(Running)	Down	1869	2.7	.9	A	N	—	—	—
Distillation Unit	(Running)	Down	1486	3.4	2.5	A	N	—	—	—
Tank 51	(Running)	Down	927	2.2	1.9	A	N	—	—	—
Tank 55	(Running)	Down	9479	2.6	2.6	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Jaime N Cocca
Date of Inspection: 11/18/15	Time: 5Am
Shift: (First or Second)	
Monitor ID:	MiniRae 2000
Instrument Calibration Gases: Isobutylene	100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	1984	1.4		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1970	1.2	1.9	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1881	3.3	.7	A	N	—	—	—
Distillation Unit	Running ✓	Down	511	3.8	2.8	A	N	—	—	—
Tank 51	Running ✓	Down	941	2.0	1.1	A	N	—	—	—
Tank 55	Running ✓	Down	9487	2.5	2.3	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Paul Lork
Date of Inspection: 11-16-15	Time: 3:00pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	n	—	—	—
SDS Shredder	Running	Down	1974	1.2		A	n	—	—	—
ATDU / OWS	Running	Down	1965	.9	1.8	A	n	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1891	2.9	1.0	A	n	—	—	—
Distillation Unit	Running	Down	480	3.2	2.7	A	n	—	—	—
Tank 51	Running	Down	927	2.3	1.9	A	n	—	—	—
Tank 55	Running	Down	9481	2.5	2.6	A	n	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Chema Saucedo
Date of Inspection: 11/19/15 Time: 6AM
Shift: (First or Second)
Monitor ID: Mini Rae 2000
Instrument Calibration Gases: Isobutylene 100 ppm
Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running X	Down	0	0		A	N	—	—	—
SDS Shredder	Running X	Down	421	.8		A	N	—	—	—
ATDU / OWS	Running X	Down	1846	—	1.7	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running X	Down	1781	2.3	1.2	A	N	—	—	—
Distillation Unit	Running X	Down	891	2.1	.7	A	N	—	—	—
Tank 51	Running X	Down	1237	2.7	.5	A	N	—	—	—
Tank 55	Running X	Down	1642	3.1	1.8	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Paul Lark
Date of Inspection: 11-19-15 Time: 5:00 pm
Shift: (First) or Second)
Monitor ID: Mini Rae 2000
Instrument Calibration Gases: Isobutylene 100 ppm
Background Instrument Reading: 0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running ✓	Down	0	0		A	n	—	—	—
CARBON OR FLARE*										
SDS Shredder	Running	Down	1980	1.3		A	n	—	—	—
ATDU / OWS	Running	Down	1969	1.2	2.1	A	n	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1878	3.2	.9	A	n	—	—	—
Distillation Unit	Running	Down	301	3.6	2.6	A	n	—	—	—
Tank 51	Running	Down	939	1.9	1.0	A	n	—	—	—
Tank 55	Running	Down	9486	2.4	2.3	A	n	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Chema Saucedo
Date of Inspection: 11-20-15	Time: 6AM
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running X	Down	0	0		A	N	–	–	—
SDS Shredder	Running X	Down	421	1.7		A	N	–	–	—
ATDU / OWS	Running X	Down	1347	—	2.1	A	N	–	–	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running X	Down X	1321	1.17	0	A	N	–	–	—
Distillation Unit	Running X	Down	412	.5	0	A	N	–	–	—
Tank 51	Running X	Down	714	2.1	.8	A	N	–	–	—
Tank 55	Running X	Down	1018	2.7	.7	A	N	–	–	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Paul Lark
Date of Inspection: 11-20-15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID:	Minirae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down	0	0		A	n	–	–	–
CARBON OR FLARE*	Running	Down				A	n	–	–	–
SDS Shredder	Running	Down	1976	1.3		A	n	–	–	–
ATDU / OWS	Running	Down	1966	1.3	2.0	A	n	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1872	3.0	1.0	A	n	–	–	–
Distillation Unit	Running	Down	303	3.7	2.6	A	n	–	–	–
Tank 51	Running	Down	942	2.0	1.1	A	n	–	–	–
Tank 55	Running	Down	9400	9.4	2.3	A	n	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Chema Saucedo
Date of Inspection: 11/21/15	Time: 6AM
Shift: (First or ~~Second~~)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR ~~FLARE~~*	Running X	Down	0	0		A	N	—	—	—
SDS Shredder	Running X	Down	387	1.2		A	N	—	-	—
ATDU / OWS	Running X	Down	1347	—	2.1	A	N	—	-	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running X	Down	1278	3.1	1.1	A	N	-	—	—
Distillation Unit	Running X	Down	1112	2.1	.7	A	N	—	—	—
Tank 51	Running X	Down	1017	1.8	.6	A	N	—	—	—
Tank 55	Running X	Down	1321	3.7	1.8	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

ondition D.1.10 Carbon Adsorber/Canister Monitoring
ondition D.1.17 Record Keeping Requirements (c)
adebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, nd the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

.1.14 CARBON ADSORPTION SYSTEM INSPECTION

spector: Smelko	
ate of Inspection: Nov 21, 15	Time: 5PM
hift: (First or Second)	
Monitor ID: Mini Rae 2000	
nstrument Calibration Gases: 100 ISOBUTYLENE/100ppm	
ackground Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
apor Recovery System:	Running ✓	Down	0	0		A	N	—	—	—
CARBON OR FLARE*	Running ✓	Down	388	1.7		A	N	—	—	—
SDS Shredder	Running ✓	Down	9268	0	4.1	A	N	—	—	—
ATDU / OWS	Running ✓	Down	1399	4.6	9.2	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1728	3.1	18	A	N	—	—	—
Distillation Unit	Running ✓	Down	1920	2.1	1.1	A	N	—	—	—
Tank 51	Running ✓	Down	8715	3.8	2.0	A	N	—	—	—
Tank 55										

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	M. PHILLIPS
Date of Inspection: 11-22-15	Time: 5 AM
Shift: (First or Second)	SECOND
Monitor ID:	MINI RAE 2000
Instrument Calibration Gases:	ISOBUTYLENE 100 PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device			Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System:			Running	Down	0	0		A	N	—	—	—
CARBON OR FLARE*												
SDS Shredder			Running	Down	391	1.8		A	N	—	—	—
ATDU / OWS			Running	Down	9281	0	4.2	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)			Running	Down	1404	4.6	1.3	A	N	—	—	—
Distillation Unit			Running	Down	1722	3.0	1.7	A	N	—	—	—
Tank 51			Running	Down	1903	2.0	.1	A	N	—	—	—
Tank 55			Running	Down	8695	3.7	1.8	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	George A Sanchez
Date of Inspection: 11/22/15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running ✓	Down	⊘	⊘		A	N	–	–	–
CARBON OR FLARE*										
SDS Shredder	Running ✓	Down	287	1.7		A	N	–	–	–
ATDU / OWS	Running ✓	Down	8967	⊘	4.3	A	N	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1538	4.8	1.2	A	N	–	–	–
Distillation Unit	Running ✓	Down	1745	2.1	1.8	A	N	–	–	–
Tank 51	Running ✓	Down	2715	2.4	.2	A	N	–	–	–
Tank 55	Running ✓	Down	8817	4.1	2.1	A	N	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	M. PHILLIPS
Date of Inspection: 11-23-15	Time: 5 AM
Shift: (First or Second)	
Monitor ID:	MINI RAE 2000
Instrument Calibration Gases:	ISOBUTYLENE 100PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down ✓	0	0		A	N	—	—	—
SDS Shredder	Running	Down ✓	257	1.7		A	N	—	—	—
ATDU / OWS	Running	Down ✓	8967	0	4.3	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down ✓	1538	4.8	1.2	A	N	—	—	—
Distillation Unit	Running	Down ✓	1745	.1	1.0	A	N	—	—	—
Tank 51	Running	Down ✓	2715	2.4	.2	A	N	—	—	—
Tank 55	Running	Down ✓	8817	4.1	2.1	A	N	—	—	—

D.1. SDS I DAILY CARBON AD[illegible]PTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	George A Sanchez
Date of Inspection: 11/23/15	Time: 5:00 pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.6

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down ✓	0	0		A	N	–	–	–
~~SDS~~ Shredder	Running	~~Down~~	96	1.2		A	N	–	–	–
ATDU / OWS	Running ✓	Down	8721	0	4.6	A	N	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	10744	5.0	1.2	A	N	–	–	–
Distillation Unit	Running	Down ✓	1762	.1	1.9	A	N	–	–	–
Tank 51	Running ✓	Down	2816	28	.4	A	N	–	–	–
Tank 55	Running ✓	Down	8992	42	2.2	A	N	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

ondition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, nd the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

.1.14 CARBON ADSORPTION SYSTEM INSPECTION

nspector: Smelco	
Date of Inspection: Nov 24, 15	**Time** 5 ~~AM~~ PM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
nstrument Calibration Gases: ISOBUTYLENE 100ppm	
ackground Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down ✓	0	0		A	N	N	–	–
SDS Shredder	Running	Down ✓	500	1.9		A	N	N	–	–
ATDU / OWS	Running	Down	9999	1.0	4.4	A	N	N	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1629	4.9	1.4	A	N	N	–	–
Distillation Unit	Running	Down ✓	1999	.2	1.9	A	N	N	–	–
Tank 51	Running	Down ✓	2919	3.4	.3	A	N	N	–	–
Tank 55	Running	Down ✓	9261	4.3	2.3	A	N	N	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

ondition D.1.10 Carbon Adsorber/Canister Monitoring
ondition D.1.17 Record Keeping Requirements (c)
radebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, nd the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Paul Lentz
Date of Inspection: 11-26-15	Time: 5:00 AM
Shift: (First or Second)	
Monitor ID:	MiniRae 2000
Instrument Calibration Gases:	Isobutylene 100 ppm
Background Instrument Reading:	0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down —	0	0		A	N	—	—	—
CARBON OR FLARE*										
SDS Shredder	Running	Down	258	1.6		A	N	—	—	—
ATDU / OWS	Running	Down	5955	0	4.2	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	5541	41.7	1.1	A	N	—	—	—
Distillation Unit	Running	Down	1750	.2	1.3	A	N	—	—	—
Tank 51	Running	Down	21058	2.2	.3	A	N	—	—	—
Tank 55	Running	Down	8501	3.9	2.2	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

ondition D.1.10 Carbon Adsorber/Canister Monitoring
ondition D.1.17 Record Keeping Requirements (c)
adebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, nd the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

.1.14 CARBON ADSORPTION SYSTEM INSPECTION

nspector:	Paul Lark
ate of Inspection: 11-23-15	Time: 5:00 AM
hift: (First or Second)	
Monitor ID:	Mini Rae 2000
nstrument Calibration Gases:	Isobutylene 100ppm
ackground Instrument Reading:	0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down								
CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	2600	1.5		A	N	—	—	—
ATDU / OWS	Running	Down	8891	0	3.9	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1322	4.0	1.0	A	N	—	—	—
Distillation Unit	Running	Down	1654	.1	1.1	A	N	—	—	—
Tank 51	Running	Down	7679	2.0	.1	A	N	—	—	—
Tank 55	Running	Down	8761	3.7	2.0	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

ondition D.1.10 Carbon Adsorber/Canister Monitoring
ondition D.1.17 Record Keeping Requirements (c)
adebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, nd the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Nov 25 '15	Time: 500
Shift: (First or Second)	
Monitor ID: MiniRae 2000	
Instrument Calibration Gases: Isobutylene	
Background Instrument Reading: 00	

Location of Carbon Control Device		Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
								Y/N	Date	Time	
Vapor Recovery System:		Running ✓	Down	0	0		A	N	–	–	–
CARBON OR FLARE*											
SDS Shredder		Running ✓	Down	299	1.7		A	N	–	–	–
ATDU / OWS		Running ✓	Down	9999	0	4.5	A	N	–	–	–
Area 8 - Tanks 52,53,54		Running ✓	Down	1600	4.7	12	A	N	–	–	–
(Tanks 02 through 04) Distillation Unit		Running ✓	Down	1729	2	1.5	A	N	–	–	–
Tank 51		Running ✓	Down	2799	2.4	3	A	N	–	–	–
Tank 55		Running ✓	Down	9215	3.9	2.4	A	N	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: M. PHILLIPS	
Date of Inspection: 11-26-15	Time: 5 AM
Shift: (First or (Second))	
Monitor ID: MINI RAE 3000	
Instrument Calibration Gases: ISOBUTYLENE 100 PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	(Running)	Down	~~0~~	~~0~~		A	N	—	—	—
SDS Shredder	(Running)	Down	265	1.5		A	N	—	—	—
ATDU / OWS	(Running)	Down	8903	~~0~~	4.0	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	(Running)	Down	1341	3.8	1.1	A	N	—	—	—
Distillation Unit	(Running)	Down	1673	.1	1.2	A	N	—	—	—
Tank 51	(Running)	Down	2704	2.1	.1	A	N	—	—	—
Tank 55	(Running)	Down	8758	3.8	2.1	A	N	—	—	—

D.1. SDS I DAILY CARBON AD[illegible]PTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: George A Sanchez
Date of Inspection: 11/26/15 Time: 5:00pm
Shift: (First) or Second)
Monitor ID: Mini Rae 2000
Instrument Calibration Gases: Isobutylene 100ppm
Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE	Running ✓	Down	&	&		A	N	—	—	—
SDS Shredder	Running ✓	Down	312	1.7		A	N	—	—	—
ATDU / OWS	Running ✓	Down	8574	&	4.6	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1482	3.7	1.4	A	N	—	—	—
Distillation Unit	Running ✓	Down	1786	&	1.6	A	N	—	—	—
Tank 51	Running ✓	Down	2815	2.4	&	A	N	—	—	—
Tank 55	Running ✓	Down	8624	3.9	2.2	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Alex Bautista
Date of Inspection: 11/27/15 Time: 5Am
Shift: (First or ~~Second~~)
Monitor ID: mini Rae 2000
Instrument Calibration Gases: Isobutylene 100ppm
Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	(Running)	Down	0	0		A	N	—	—	—
CARBON OR (FLARE)*										
SDS Shredder	(Running)	Down	.287	1.6		A	N	—	—	—
ATDU / OWS	(Running)	Down	9980	—	2.2	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	(Running)	Down	1589	3.4	1.3	A	N	—	—	—
Distillation Unit	Running	(Down)	.2	2.2	.8	A	N	—	—	—
Tank 51	(Running)	Down	2099	1.9	.6	A	N	—	—	—
Tank 55	(Running)	Down	9145	3.8	1.9	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Smelko
Date of Inspection: Nov 27	Time: 5PM
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	ISOBUTYLENE 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running ✓	Down	0	0		A	W	—	—	—
CARBON OR FLARE*										
SDS Shredder	Running ✓	Down	1371	2.0		A	W	—	—	—
ATDU / OWS	Running ✓	Down	9999	0	2.6	A	W	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1560	3.6	1.3	A	W	—	—	—
Distillation Unit	Running	Down ✓	70	2.2	1.0	A	W	—	—	—
Tank 51	Running ✓	Down	3428	1.7	2.1	A	W	—	—	—
Tank 55	Running ✓	Down	8926	4.10	30	A	W	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: M. PHILLIPS
Date of Inspection: 11-28-15 Time: 5 AM
Shift: (First or Second)
Monitor ID: MINI RAE 2000
Instrument Calibration Gases: ISOBUTYLENE 100 PPM
Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down	0	0		A	N	—	—	—
CARBON OR FLARE*										
SDS Shredder	Running	Down	290	1.7		A	N	—	—	—
ATDU / OWS	Running	Down	9891	.1	2.1	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1597	3.3	1.4	A	N	—	—	—
Distillation Unit		Down	.1	2.1	.7	A	N	—	—	—
Tank 51	Running	Down	2703	1.8	.5	A	N	—	—	—
Tank 55	Running	Down	9137	3.7	1.7	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

ondition D.1.10 Carbon Adsorber/Canister Monitoring
ondition D.1.17 Record Keeping Requirements (c)
radebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, nd the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	George A Sanchez
Date of Inspection: 11/28/15	Time: 5:00pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down								
CARBON OR FLARE*		X	0	0		A	N	—	—	—
SDS Shredder	Running	Down								
		X	97	.9		A	N	—	—	—
ATDU / OWS	Running	Down								
		X	1742	.2	2.1	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down								
	X		1284	3.8	1.7	A	N	—	—	—
Distillation Unit	Running	Down								
		X	22	1.9	.6	A	N	—	—	—
Tank 51	Running	Down								
	X		3189	2.2	.7	A	N	—	—	—
Tank 55	Running	Down								
	X		4284	4.1	1.9	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

ondition D.1.10 Carbon Adsorber/Canister Monitoring
ondition D.1.17 Record Keeping Requirements (c)
radebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, nd the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Alex Bautista	
Date of Inspection: 11/29/15	Time: 5 AM
Shift: (First or Second)	
Monitor ID: mini Rae 2000	
Instrument Calibration Gases: 100ppm Isobutylene	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running ✓	Down	d	d		A	N	—	—	—
CARBON OR FLARE*										
SDS Shredder	Running ✓	Down	305	1.6		A	N	—	—	—
ATDU / OWS	Running ✓	Down	2814	2.4	2.7	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1894	3.9	2.2	A	N	—	—	—
Distillation Unit	Running ✓	Down	24	1.8	.65	A	N	—	—	—
Tank 51	Running ✓	Down	2189	2.6	.9	A	N	—	—	—
Tank 55	Running ✓	Down	5041	4.6	2.4	A	N	—	—	—

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

ondition D.1.10 Carbon Adsorber/Canister Monitoring
ondition D.1.17 Record Keeping Requirements (c)
radebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, nd the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	George A Sanchez
Date of Inspection: 11/29/15	Time: 5:00pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down								
CARBON OR FLARE*	✓		X	X		A	N	–	–	–
SDS Shredder	Running ✓	Down	317	1.7		A	N	–	–	–
ATDU / OWS	Running ✓	Down	2984	2.7	2.9	A	N	–	–	–
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1862	4.1	2.0	A	N	–	–	–
Distillation Unit	Running	Down ✓	29	1.7	.5	A	N	–	–	–
Tank 51	Running ✓	Down	2214	2.4	.9	A	N	–	–	–
Tank 55	Running ✓	Down	5137	4.4	2.3	A	N	–	–	–

D.1. SDS I DAILY CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Alex Bautista SR
Date of Inspection: 11/30/15	Time: 5 4m
Shift: (First or Second)	5 4m
Monitor ID:	MINI RAE 2000
Instrument Calibration Gases: 100 PPM	Isobutylene
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	d	d		A	N	—	—	—
SDS Shredder	Running ✓	Down	302	1.4		A	N	—	—	—
ATDU / OWS	Running ✓	Down	2876	2.6	3.1	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1901	4.8	1.8	A	N	—	—	—
Distillation Unit	Running	Down ✓	34	1.4	2.8	A	N	—	—	—
Tank 51	Running ✓	Down	2344	3.0	3.0	A	N	—	—	—
Tank 55	Running ✓	Down	4876	4.0	4.2	A	N	—	—	—

D.1. SDS I DAILY CARBON AD[illegible]PTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
Tradebe shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. Tradebe shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	George A Sanchez
Date of Inspection: 11/30/15	Time: 8:00 pm
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100 ppm
Background Instrument Reading:	0-0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	X	X		A	N	—	—	—
SDS Shredder	Running ✓	Down	372	1.8		A	N	—	—	—
ATDU / OWS	Running ✓	Down	2986	2.7	3.4	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1764	5.6	2.1	A	N	—	—	—
Distillation Unit	Running ✓	Down	125	1.9	2.9	A	N	—	—	—
Tank 51	Running ✓	Down	2462	3.2	2.9	A	N	—	—	—
Tank 55	Running ✓	Down	5151	4.4	4.6	A	N	—	—	—